



## CG-90 GENERAL PURPOSE CLEAR GREASE WITH PTFE

CG-90 is a clear, low odour, general purpose grease for superior lubrication. Exhibits excellent adhesion, high tack strength, penetrates quickly and thickens to form a long-lasting lubricating coating.

CG-90 contains PTFE which greatly enhances lubrication performance and reduces friction. CG-90 has excellent thermal stability and is resistant to hot water, steam, acids and alkalis preventing corrosion. Wide operating temperature range from -12°C to +180°C and will not break down under high pressures.

### KEY FEATURES

- General purpose EP clear grease
- Contains PTFE to enhance lubrication performance
- Thermally stable with an operating temperature range from -12°C to +180°C
- Locks-out moisture and prevents corrosion

### MARKET SECTORS:

**INDUSTRIAL MRO**  
**TRADE/PRO-DIY**  
**ELECTRICAL MRO**  
**FASTENERS & FIXINGS**  
**AGRICULTURE**

AC CODE	CRC CODE	SIZE
1955	32799	500ml Aerosol

## NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

### APPLICATION AREAS

Use for the lubrication of a wide variety of bearings, hinges, small gears and sliding metal parts.

### DIRECTIONS FOR USE

- Shake well before use.
- Do not use on energised/moving equipment.
- Spray the component to be lubricated.
- Allow CG-90 to penetrate then thicken before restarting machinery.

APPEARANCE:	Clear grease
ODOUR:	Odourless
SPECIFIC GRAVITY AT 20°C:	0.860
TEMPERATURE RANGE:	-12 °C to +180 °C
SOLUBILITY:	Insoluble in water

(All values apply to product without aerosol propellant)

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/cg-90/> or from [info.uk@crcind.com](mailto:info.uk@crcind.com)

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

## TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

