



CT-90 CUTTING & TAPPING FLUID

CT-90, the ultimate 4-in-1 versatile cutting lubricant makes metal working easier when cutting, tapping, drilling and reaming. High-performance metal cutting lubricant for use on all tough metals including stainless steel. Specially formulated with excellent extreme-pressure (EP), additives reducing friction and keeping the workpiece at a stable temperature to prevent seizing. Dissipates heat, reducing cutting time, swarf build-up, metal scrap and downtime. Protects and extends the life of the tool.

KEY FEATURES

- Versatile, multi-metal cutting, tapping, drilling and reaming lubricant
- Reduces friction and cutting time
- Improves surface finish
- Extends tool life
- Dissipates heat and reduces swarf build-up
- Available as a spray, liquid, and compound

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

MARKET SECTORS:

FASTENERS & FIXINGS

ENGINEERING

TRADE/PRO-DIY

ELECTRICAL MRO

AGRICULTURE

AC CODE	CRC CODE	SIZE
-	33324	500ml Aerosol TwinSpray
1846	32772	500ml Aerosol
1495	32865	5L bulk can
1483	32862	500ml Bottle with spout
1528	32861	480g Compound Tub

APPLICATION AREAS

All types of stainless steels, carbon steels and Nimonic alloys. Can also be used as a deep drawing, blanking or piercing lubricant.

CT-90 Aerosol

Convenient easy to apply, for precise application control, and hard-to-reach areas. Ideal for mobile engineers and operators working off-site.

CT-90 Fluid

Packed in a convenient spout top squeeze bottle or in a bulk can for flood lubrication. Ideal for difficult cutting operations that require an extreme pressure additive.

CT-90 Compound

A heavy duty viscous non-drip paste which can be applied by brush or by dipping the tool or bit into the compound.

DIRECTIONS FOR USE

- Apply to the cutting tool before the cutting operation begins and to the workpiece during cutting.
- Exercise caution when applying near moving parts.
- CT-90 may cause staining on some yellow metals.

CT-90 aerosol

- Gently shake the aerosol can and spray in an upright position.

CT-90 poly bottle and bulk can

- Apply CT-90 fluid before use and also during operations.

CT-90 compound

- Apply by using a brush to the work, or dip the cutting tool or bit directly into the compound.

	AEROSOL	POLY BOTTLE	COMPOUND	BULK
APPEARANCE:	Dark amber liquid	Dark amber liquid	Dark amber paste	Dark amber liquid
ODOUR:	Characteristic	Characteristic	Characteristic	Characteristic
SPECIFIC GRAVITY:	0.870 @ 20°C	1.050 @ 15°C	1.045 @ 60°C	1.050 @ 15°C
VISCOSITY	26 mm ² /s @ 40°C	144 mm ² /s @ 40°C	No data currently available	144 mm ² /s @ 40°C
SOLUBILITY:	Insoluble in water	Insoluble in water	Insoluble in water	Insoluble in water
FLASH POINT:	>220°C	>192°C	>192°C	>192°C
POUR POINT	- 12°C	- 5°C	Not applicable	- 5°C

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/ct-90/> or from info.uk@crcind.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

