

OIL TREATMENT

Spanjaard Oil Treatment is an oil additive that improves oil viscosity at high temperatures. It also contains a soluble molybdenum compound which aids in reducing wear. It is designed to enhance the performance and longevity of engine oil.

APPLICATIONS

- Improves lubrication
- Reduces oil consumption and exhaust smoke in worn motors
- Increases engine compression
- Reduces wear
- Cushions regular impact areas such as tappets, cams and gears

DIRECTIONS FOR USE

1. Change oil if required.
2. Run the engine until it reaches operating temperature
3. Add a full bottle of **Spanjaard Oil Treatment**.

PROPERTIES

| | |
|------------------|--|
| Colour: | Green— tinge of brown |
| Features: | <ul style="list-style-type: none"> • Appearance: Liquid • Specific gravity (25°C): 0.92 • Viscosity (cSt, 25°C): 3700 |

PACKAGING

375 ml Bottle
5 L plastic container



Revision: 241123

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

